

Concrete Production





Concrete Production


- ASTM C94 - why?
- Specifications for ready mix most closely align with our product mix and production concepts
- Good starting point for specifications rather than inventing new ones





Redi-mix Requirements

- Consistent Aggregates
- Aggregates Stored Properly
- Accurate Mix Proportions
- Consistently Mixed
- Transported to the forms






Concrete Production Topics

Material Handling
Batching
Mixing
Transporting





Quality School



Material Storage And Handling





Proper Aggregate Storage


- Minimize Segregation
 - . Do not store in conical piles
 - . Store in horizontal layers
- Prevent Contamination
 - . Store on slabs or planking
 - . Have storage bins separated by walls
- Keep gradations within specified limits
- Reference ACI 304, “Guide for Measuring and Placing Concrete”








Quality School



Stockpiles that stack traditionally can segregate, with **coarser material falling to the bottom/outside, and finer material remaining in the center and top**. Degradation can occur if loaders or dozers drive onto the stockpile, or if material is falling from a great height — potentially splitting or crushing the graded material. Equipment driving on stockpiles can also cause contamination, as it tracks dirt or loose material onto the stockpile.






WOW!



Quality School



Correct loading techniques gathers a blend and does not hurt the pile




Flat Stacks













Quality School




Under the individual grizzlies will be a system similar to this. The storage bins are directly under the truck dump areas and feed into individual weigh hoppers or onto a cumulative weigh belt that leads to the mixer








Filling Aggregate Bins




Correct



Incorrect



Quality School



Batching





Batching

- Accuracy of weighing
- Compensating for moisture in Aggregates
- Sequencing





Typical Batching Tolerances (C94)

- **Cementitious** $\pm 1\%$
(for batches less than 1cy not less than required, up to 4% over)
- **Water** $\pm 1\%$
- **Fine Aggregates** $\pm 2\%$
- **Coarse Aggregates** $\pm 2\%$
- **Cum. Aggregates** $\pm 1\%$
- **Admixes** $\pm 3\%$
(or minimum recommended dosage per 100 weight or which ever is greater)





Accuracy

- Scales must hang free
- Scales (gates or valves) must not leak
- Scales must empty completely after each batch
- Zero on scales should be checked on a regular basis
- Calibrate scales annually





Why Compensate for Moisture in Aggregates?

- Batch Consistency
- Predictable strengths
- Production efficiency





Free Moisture

- The **free moisture** must be accounted for when batching our concrete to help control mix costs and to improve its quality and consistency





Free Moisture Example

- Consider the amount of water in **1,854** pounds of sand
(which is a typical amount of sand for a yard of pipe machine concrete)
that has **4%** total moisture in it and has an absorption of **1%**
- This gives us free moisture of **3%** (4%-1%)





Free Moisture Example

- At 3% moisture:
- The 1,854 pounds of sand that we weighed up is 1800 pounds of SSD sand and 54 pounds of water
- Fifty-four pounds of water is 6 ½ gallons (54pounds/8.33 pounds per gallon) of water
- We are 54 pounds short of sand and we have 54 extra pounds of water
- If we do not compensate properly for this difference, it will significantly affect the cost and quality of the concrete that we are producing





Compensating for Moisture in Aggregates

The old fashioned way

- Water Valve (hose)
- No compensation for lost (yield) aggregate
- Inconsistent mixes (slump)
- Inconsistent strengths due to varying batch proportions and W/Cm ratio





Compensating for Moisture in Aggregates without Probes

Daily burn offs of aggregate samples

- Compensation for moisture in aggregates remains constant as long as moisture does not change between burn offs
- Can improve batch consistency (slump)
- Can improve strength consistency






Compensating for Moisture in Aggregates

Moisture Probes


- Good batch consistency (Slump)
- Automatic compensation for Aggregates
- More consistent strengths
- Probes need to be calibrated and calibration must be checked on a routine basis based on requirements from your local agencies.




Microwave Bin Probe Calibration Plots




- Typical Sand Microwave Bin Probe Plot




Microwave Bin Probe Quality Plots




- Typical Rock Microwave Bin Probe Plot



Microwave Bin Probe Calibration Plots



- Shifts in Probe Calibrations





Sequencing (per manufacturer's recommendation)

- Aggregates
- Cementitious
- Water
- **Admixtures** (per admix manufacturer recommendation)

- Aggregates
- Water
- Cementitious
- **Admixtures** (per admix manufacturer recommendation)

OR





Sequencing Cement

- Depends on Mixing system
- Generally cement should be discharged when all aggregates and water are in mixer
- If cement balling occurs cement should be discharged sooner or later depending on your mixer
- Ask your mixing manufacturer for a recommended sequence and timing schedule





Why does the Sequencing of Admixtures matter?

- Mix Consistency
- Reducing the amount of additive added (cost)
- How it affects the probe readings






Air Entrainment Sequencing

- Air entraining should be added with the mix water or aggregates
- Air entraining should be mixed with aggregates for a few seconds before adding cement





Quality School



Lubricant/Surfactant Sequencing (Dry Cast)

- Should be added with the aggregates and water





Water Reducer Sequencing

- Water Reducers should be added with the mix water after the air entraining is done





High Range Water Reducer (Super/Superplasticizer) Sequencing

- High Range Water Reducers should be added at the end of the batch after all ingredients are thoroughly mixed





Admixture Sequencing


- Always work with your admixture supplier when you have batching sequence questions or issues






SCC Sequencing

A Typical SCC Time Cycle Diagram for 2 Yard Batch






Quality School




It is important to understand the effect of time on your concrete. The workability and quality of the concrete will deteriorate particularly in hot weather







Quality School



Mixers





Mixer Output

- Quantity of concrete needed per day
- Quantity of concrete needed per hour





Mixer Output

- Output is measured in:
 - ft^3
 - yd^3
 - m^3
- **Typically 2/3 of rated capacity!!!**





Common Types of Mixers

- Paddle Mixers
- Ribbon/Spiral Blade Mixers
- Pan Mixers
 - Counter-Current
 - Rotating Pan
 - Stationary Pan
- Twin-Shaft Mixers





PADDLE MIXER






RIBBON MIXER






TURBINE MIXER



COUNTER CURRENT MIXER





PAN MIXER






TWIN SHAFT MIXER





Quality School




Concrete Transport







Quality School





Concrete Discharge from Mixer

Discharge into center of bucket or hopper





Handling Concrete

- Avoid
 - Segregation
 - Loss Of Mortar
 - Loss of Slump





Segregation

- Most common cause of damage occurs:
 - if concrete is not discharged vertically
 - at free-fall distances more than 6 feet
 - when jarring or shaking during transportation
- Open chutes
 - more than 20' Long
 - chutes that are too steep (slide not tumble)





Pouring Concrete

- Place concrete in the form near its final location
- Keep free-fall to a minimum
- Use flat forms
 - Begin pour at corner or edge
 - Pour in equal lifts
- Vertical Forms
 - Pour in horizontal layers
 - For large blockouts, pour on one side - allow concrete to flow underneath



Questions?

Tom Umek

Tom.Umek@cam-hp.com

